



SFP-1310S40

Article number: 216477

SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector
-40°~+75°C

Compatible to IEEE802.3z Gigabit Ethernet Standard

Bandwith 1,25Gbps

Compliant with Fibre Channel 100-SM-LC-L

Industry standard small form pluggable (SFP) package

Duplex LC connector, 1310nm

Differential LVPECL inputs and outputs

Single power supply 3.3V

Hot Pluggable

Class 1 laser product complies with EN 60825-1

Distance 9/125 µm SMF 20km

Temperature range -40° ~ +70°C

Specifications

| Interfaces / Inputs / Outputs: | |
|--------------------------------|---------------|
| Operation mode | single mode |
| Fiber optic connector | Duplex LC |
| General: | |
| Range | 20 km |
| Weight | 17g |
| Temperature range (operation) | -40°C ~ +75°C |
| Wavelength | 1310nm |
| Notes: | |
| Application | indoor |
| Number of fibers | 2 |
| Transmission medium | optical fiber |



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

