



VM-HD15P

Article number: 217912

15" (38cm) LCD Monitor HD, 1024x768, LED, HDMI, VGA, Composite

Professional 15" (38 cm) LCD monitor

Industrial design built to run 24x7x365 continuously

Maximum resolution 1024x768 pixels

LED Back Light

Fast response time 5ms

Perfect presentation through digital 3D filtering and noise reduction

Different video inputs HDMI, VGA, Composite

Supply voltage: 12VDC

Plastic cabinet including stand


Specifications

Display:	
Resolution	1024x768 (4:3)
Synchronization	internal
Aspect ratio	4:3
Resolution pixels	1024x768
Display element	Anti-Glare-Display, Hard coating (3H), Haze :25%
Contrast ratio typical	700:1
Response time typical	5 ms
Brightness typical	350 cd/m ²
Backlighting	LED
Viewing angle vertical	178 °
Viewing angle horizontal	178 °
Screen size	15"
Screen Size (cm)	38 cm
Pixel format	0,248mm x 0,248mm
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Features:	
Comb filter	3D comb filter with de-interlace
Menu languages	English
Interfaces / Inputs / Outputs:	
Video inputs (type)	VGA, HDMI, 2x composite (CVBS)
Audio inputs	1x 3.5mm jack, 1
Audio output	1x 3,5mm jack
Serial interfaces	no
General:	
Dimensions (HxWxD)	274x348,8x42,8mm
Total height with stand	328mm
Mount	VESA standard 75x75mm
Housing material	plastic
Housing color	black
Weight	2.9kg
Loudspeaker	2
Power consumption	11.5W
Supply voltage	12VDC
Temperature range (operation)	-30°C ~ +85°C, @ Humidity 10%-90% (non-condensing)
Scope of delivery:	
Parts supplied	manual, power cord, PSU 100-240VAC, IR remote controller, VGA cable, feet

Related Products



VMC-LCD/WCMB-1 | SKU: 90394



VM-LCDWMB2 | SKU: 224229



VM-TSHA | SKU: 228569



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

