

MAXIMUS MMX



- Certifications for use in Zones 1 and 2, IIB T6 or T5 Group (Gas) and in Zones 21 and 22, IIIC T85°C or T100°C Group (Dust)
- AISI 316L stainless steel construction
- Supports for ceiling, wall and parapet installation supplied
- Camera Full HD 1080p, 3x or 10x with image stabilizer

NVIF® | QST



MAXIMUM RESISTANCE IN THE MOST CRITICAL ENVIRONMENTS

HIGH QUALITY IMAGE

100% MADE IN VIDEOTEC

MECHANICAL

CABLE GLANDS

HOUSING'S WINDOW

ELECTRICAL

NETWORK

CYBERSECURITY

VIDEO

CAMERAS

CABLE GLANDS AND ACCESSORIES 1/2" NPT

Type	Certification	Operating temperature	Cable	Model Number	Diameter of the external cable	Under armor cable diameter

MAXIMUS MMX CERTIFICATIONS AND MARKINGS WITH CABLE

Certification	Marking	Ambient temperature

MAXIMUS MMX CERTIFICATIONS AND MARKINGS WITHOUT CABLE

Certification	Marking	Ambient temperature

MAXIMUS MMX CONFIGURATION OPTIONS

	Voltage	Camera	Connections	Video Output	
MMX	2	C	0	Z	A
		D	A		
			B		

