



IAM-5SE1004MUC

Article number: 220212

Gigabit Switch, Unmanaged, 4x PoE, 2x RJ45 and 2x SFP, 1000Mbps, Industrial Design

Gigabit PoE switch, DIN Rail

Gigabit Uplink ports 2xRJ45, 2xSFP

4x 10/100/1000 PoE Ports, IEEE 802.3af/at

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

Temperature range -40° C ~ +75° C

Specifications

| Features: | |
|--------------------------------------|--|
| Multicast compliant | no |
| Port mirror | no |
| QoS | no |
| SNMP | no |
| Network: | |
| Ethernet Standards | IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT, IEEE 802.3z 1000BaseSX/LX, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE) |
| Internal switching capacity (Mpps) | 10,4 Mpps |
| Internal switching capacity (Gbit/s) | 14 Gbps |
| VLAN | yes |
| Interfaces / Inputs / Outputs: | |
| Ethernet interface | 10Base-T, 100Base-TX, 1000Base-T |
| Ports | 4x 10/100/1000Base-T, 2x 10/100/1000T SFP, 2x 10/100/1000Base-TX |
| Optical connection | SFP Port |
| General: | |
| Dimensions (HxWxD) | 46x110x163mm |
| 19" Rack mountable | no |
| Number PoE ports | 4 |
| Model | DIN rail module |
| Type | Layer2 switch |
| Weight | 530g |
| Blower | no |
| Management | no |
| Mounting | DIN rail, wall mount |
| PoE Power | 120 W |
| Power over Ethernet | IEEE 802.3at |
| Supply voltage | 48-57 VDC |
| Temperature range (operation) | -40°C ~ +75°C |
| Scope of delivery: | |
| Parts supplied | manual, power cord, Mounting Bracket, PSU |
| Notes: | |
| Application | indoor |

Related Products



DRP-240-48 | SKU: 214832

Product recommendations



SFP-1310S40|SKU: 216477



SFP-1310M40|SKU: 216478



SFP-0850M10|SKU: 216479



SFP-1310S10|SKU: 216566



SFP-0850M40|SKU: 218758



RJT-1000SFP|SKU: 219525

