

SOL-IQbox-eco/Hz

Article number: 220522

Camera junction box for
video surveillance 400x300x150mm with
outlet, FI/LS and heating

Optimised for outdoor use
Electrically prewired for flexible, modular expansion.
UV stable polycarbonate, corrosion-resistant
Protective class IP66
Impact resistance IK 10, vandalism protected
Swivelling door (with door contact switch)
Wall or mast mounted
Fast, easy installation
Simple mechanical finishing

Junction box for universal expansion with a variety of components from different manufacturers and in different designs. The additional components may be mounted either on mounting plates using hook and loop strap without requiring tools, or using a TS35 mounting rail, which is also included in the scope of delivery.

Specifications

Housing:	UV resistant polycarbonate, RAL 7035, seal: PUR
Door:	Swivelling, opening angle 120°
Closure:	2-point closure, double bit
Exterior dimensions:	400 x 300 x 150mm
Protective class:	IP66, IK10
Temperature range	-50°C to +70°C
Cable glands:	1 x M16x1.5 3 x M20x1.5 1 x M25x1.5 1 x M25x1.5 – separable (suitable for network wiring) All cable entries ex works incl. sealing plugs
Voltage input:	230V/50Hz
1. Mounting rail TS35:	With terminals, mounted, 20mm elevated for placing cables underneath
2. Mounting rail TS35:	With included fastening materials
Service outlet	Protective contact outlet
Personnel protection:	FI Circuit breaker Siemens 5SU1354-6KK16
Other:	Door alarm contact, mounted and wired to terminals, 3x hook and loop strap, 2x pressure compensation element mounted

© Copyright **Solvido** by VIDEOR E. Hartig GmbH
07 March 2023 11:59:00 | We reserve the right to make technical changes

Optional accessories

209744 SOL-WST-MB-30	Mast attachment 30cm
209743 SOL-WST-WB	Wall mounting
220068 SOL-WST-SSK/1	Lock with toggle closure (piece) with key NOTE: 2 pieces are required
219463 SOL-SSK-ES-30	Grounding set for locks SOL-WST-SSK

Connection box:

As SOL-IQbox-eco-B, but additionally with accessories already installed:

211113 SOL-WST-HT Heater and thermostat 230V/22W.

Temperature range: -35°C to +45°C

© Copyright **Solvido** by VIDEOR E. Hartig GmbH
07 March 2023 11:59:00 | We reserve the right to make technical changes

Your contact person

Solvido is a registered trademark of