



SOL-IQbox-mini/Hz

Article number: 221320

Camera junction box for
video surveillance incl. heating
300x200x150mm

Optimised for outdoor use
Electrically prewired for flexible, modular expansion.
UV stable polycarbonate, corrosion-resistant
Protective class IP66
Impact resistance IK 10, vandalism protected
Swivelling door (with door contact switch)
Wall or mast mounted
Fast, easy installation
Simple mechanical finishing

Junction box for universal expansion with a variety of components from different manufacturers and in different designs. Additional components can be mounted on another TS35 mounting rail.

Specifications

Housing:	UV resistant polycarbonate, RAL 7035, seal: PUR
Door:	Swivelling, opening angle 120°
Closure:	1-point closure, double bit
Exterior dimensions:	300 x 200 x 150mm
Protective class:	IP66, IK10
Heating:	10W
Temperature range:	-50°C to +70°C
Cable glands:	1 x M20x1.5 2 x M25x1.5 – with separable insert
Voltage input:	230V/50Hz
1. Mounting rail TS35:	With terminals, mounted, 20mm elevated for placing cables underneath
2. Mounting rail TS35:	Empty, for fitting with any additional components.
Safeguard:	Circuit breaker Siemens 5SY4116-6
Other:	1x pressure compensation element mounted

Optional accessories


212371 SOL-WST-MB-20	Mast attachment 20cm
209743 SOL-WST-WB	Wall mounting

Connection box

as SOL-IQbox-mini-B, but additionally with already installed heating and thermostat 230V/10W
(not available separately as accessories)

Temperature range: -50°C to +60°C

Your contact person

 The logo for SOLVIDO, featuring a stylized purple circular icon to the left of the word "SOLVIDO" in a bold, black, sans-serif font, with a registered trademark symbol (®) to the upper right of the word.	<p>Solvido is a registered trademark of VIDEOR E. Hartig GmbH Carl-Zeiss-Straße 8 63322 Rödermark Germany Phone: +49 6074-888-111 E-mail: info@videor.com Website: www.videor.com</p>
---	--