



IAM-6MC1001MRA

Article number: 221577

Ethernet Coax Receiver Data & Power over Coax 1 x RJ-45, 1 x BNC

EPOC Ethernet and Power over Coax Transmission	PoE/PoE+ Power Supply for Transmitter
RJ45 Ethernet and BNC-Female plug	128 Bit AES Network Encryption
Max. Transmission Rate 95Mbps Full Duplex	Supports Multi Connection (Daisy Chain, Star)
Data Transmission up to 2.4Km	Surge Protection
PoC Transmission up to 1.2Km	Temperature Range (Operating) -20° C bis +60°C
Power Supply Receiver PoE or 12-57V DC	Easy Installation (Plug & Play)

Specifications

Network:	
Output power	60W max.
Data transfer rate	95 Mbps
Gigabit	no
Interfaces / Inputs / Outputs:	
External connections	RJ-45, BNC - EPOC (max. 60W out), 56VDC input (DC plug)
Ethernet interface	10Base-T, 100Base-TX
Ports	1x 10/100Base-TX, 1x BNC
PoE input	IEEE802.3af, IEEE802.3at
General:	
Series	eneo EPOC
Dimensions (HxWxD)	24x61,6x82,4mm
Model	module
Range	2400 m
Colour	anthracite
Housing	Metal
Type	Media Converter
Weight	77g
Mounting	desktop
Supply voltage	56VDC, PoE (IEEE-802.3af)
Temperature range (operation)	-20°C ~ +60°C
Parts supplied	manual
Application	indoor
Transmission medium	Coax

Related Products



IAM-4MU1001M0A|SKU: 221334



IAM-6MC1001MTA|SKU: 221576



NE-141/220VAC-57VDC|SKU: 221276



eneo EPOC Group Manager|SKU: 225117

www.eneo-security.com

More product information

Network transmission with 128bit AES encryption standard



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

