



# TSD-52F0013P0A

Article number: 221916

1/3" HD Dome, Fixed, Day&Night 1920x1080, Infrared, 1,34mm, 360°, Indoor, 12VDC

1/1,3" Progressive CMOS-Sensor	D-WDR (Digital Wide Dynamic Range)
1,34mm fixed focal length	UTC support remote control by Pelco C protocol
HD-TVI analouge fishEye camera	For ceiling and wall installation
360° surround and 180° panorama view	Compact design for indoor application
Resolution max. 1920x1080@25fps	

## Specifications

Camera:		Interfaces / Inputs / Outputs:	
Sensor size	1/3"	Video outputs	HD-TVI
Imager	CMOS, Progressive scan	External connections	12VDC input (DC plug), 1x HD Analog Signal (BNC), connection cable approx.40cm
System	True Day&Night	Alarm inputs	no
Sensitivity	0,5 Lux, at F2.0, 30 IRE	Alarm outputs	no
Low speed shutter	no	Serial interfaces	Coaxitron (HD Protocol)
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.	Serial interfaces protocols	UTC (HD signal format)
Wide Dynamic Range (WDR)	D-WDR	General:	
Day/Night switching	auto, day, night	Series	EX-Series
IR cut filter	switchable	Dimensions (HxWxD)	33,5x77mm
White balance	automatic, push lock	Illumination	infrared, 4x IR LED 850nm
Signal-to-noise ratio	50dB	Illumination range	approx. 7m
Video:		Colour (housing)	white
Signal format	HD-TVI @ 2MP	Colour (bubble)	clear
Frame rate	25/30fps @ 1920x1080p	Housing	indoor
Lens:		Housing material	plastic
Lens type	fixed focal length	Weight	345g
Focal length	1,34 mm	Heater	no
Digital zoom	no	Power consumption	3.2W
MOD (Minimum object distance)	0,3 m	Blower	no
Aperture range (F)	F2.0	Mounting	wall mount, ceiling mount
Resolution pixels	1920x1080	Supply voltage	12VDC
Horizontal angle of view	360 °	Temperature range (operation)	0°C ~ +40°C
Video standard	PAL/NTSC	Vandalism resistant	no
Features:		Scope of delivery:	
Motion detector	no	Parts supplied	manual, drilling template, screw set
Menu languages	English		
Privacy zones masking	no		
Mirror function	V flip, H-flip, H/V flip		
Digital Noise Reduction (DNR)	yes		

## Related Products



PS12DC-11 | SKU: 218653



MAM-5DC1004M0A | SKU: 225085



MAM-5MM2001M0A | SKU: 225135

## Product recommendations



TVA-1201TRA|SKU: 212984



TVA-1201TRP|SKU: 212985



MAM-5ME1001MTA|SKU: 217344



MAM-5MM1001MOA|SKU: 220299



MAM-6ME1012MTA|SKU: 219643



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)

Stay informed and subscribe  
to the eneo newsletter

