



ISD-52F0023WSA

Article number: 227007

1/2,8" Network Dome compact,, 1920x1080, Day&Night, WDR, 2,3mm, H.265, PoE, 12VDC, S


1 / 2.8 "2.0 MP Sony STARVIS CMOS sensor	Slot for micro SD memory card
Resolution max. 1920x1080 (Full HD)	ONVIF compliance, PoE IEEE802.af, 12VDC
Fixed focal length 2.3mm, day / night lens (HfOV 135 °!)	Audio, alarm inputs and outputs
Quad Streaming (H.265, H.264, MJPEG)	Privacy zones, password protection, browser-independent
Intelligent self-learning video analysis (IntelliVision inside)	Increasing the refresh rate when moving
WDR 120dB, Smart BLC	Suitable for indoor and outdoor use IP66

Specifications

Camera:		Features:	
Camera type	Dome	Audio support	yes
Sensor size	1/2,8"	Password protection	yes
Resolution standard	HD 1080p	e-PTZ support	yes
Imager	CMOS, Sony STARVIS, Sensor IMX290	Internal storage	microSDHC card, microSDXC card
System	True Day&Night	Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
Sensitivity	0,08 Lux, 40IRE	Privacy zones masking	Areas-ON/OFF switchable
Low speed shutter	yes, automatic	Remote configuration	web browser
Manual electronic shutter (MES)	1~1/10000Sek.	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
Automatic electronic shutter (ESC)	1~1/10.000sec.	User interface	Type B (white / blue)
Wide Dynamic Range (WDR)	WDR 120dB	Mirror function	H-flip, mirror
Flickerless function	yes	Digital Noise Reduction (DNR)	yes
Backlight compensation	Smart BLC	Network:	
Day/Night switching	auto, day, night	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, RTP, UPnP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS, OpenVPN
IR cut filter	switchable	Interfaces / Inputs / Outputs:	
White balance	automatic, manual	External connections	alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx.55cm
Signal-to-noise ratio	48dB	Ethernet interface	10Base-T, 100Base-TX
Video:		Alarm inputs	1
Resolution	1920x1080 (16:9), 1440x1080 (4:3), 1280x1024 (5:4), 1024x768 (4:3), 1280x720 (16:9), 800x600 (4:3), 800x480 (16:9), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 400x240 (4:3), 352x288 (4:3), 352x256 (4:3), 352x240 (4:3), 320x240 (4:3)	Alarm outputs	1
Resolution max.	1920x1080	General:	
Image display	5:4	Series	eneo SN-Series
Stream types	Quad Streaming	Dimensions (HxWxD)	91,5x120mm
Image transmission rate max.	30 fps	Illumination	no
Compression standard	H.264, H.265, H.264+ (Smart Stream), H.265+ (Smart Stream), MJPEG	Colour (housing)	white
Lens:		Colour (bubble)	clear
Lens type	fixed focal length	Housing	outdoor
Focal length	2,3 mm	Housing material	aluminium
Digital zoom	yes	Weight	880g
MOD (Minimum object distance)	0,3 m	Heater	no
Iris control	no	Power consumption	4.8W
Vertical angle of view	75 °	Blower	no
Horizontal angle of view	135 °	Mounting	wall mount, ceiling mount
DORI:		ONVIF	ONVIF Profile S, ONVIF Profile T
Detection (25 px/m)	35 m	Power over Ethernet	IEEE 802.3af
Observation (62 px/m)	14 m	Protection rating	IP66
Recognition (125 px/m)	8 m	SDK	upon request
Identification (250 px/m)	4 m	Supply voltage	12VDC, PoE
Features:		Temperature range (operation)	-20°C ~ +50°C
Multicast compliant	yes	Text display	supplied
Motion detector	yes	Vandalism resistant	yes
Analysis functions	motion detection, motion analysis, intrusion, tampering protection, Defog, Digital Image Stabilization	Certificates	IK10
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out	Scope of delivery:	
Audio	2 Way Audio	Parts supplied	manual, bag of screws

Related Products

Product recommendations



eneo Site Manager | SKU: 218218



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

