



IPD-68M3611P5A

Article number: 227050

1/2,5" Network Dome, Fix, 3840x2160, Day&Night, DOL-WDR, 3,6-11mm, Infrared, Indoor

1/2.5" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 3840x2160, 8 Megapixel	Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 3.6~11mm	Slot for Micro SD Card, HTML5 replay
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE or 12VDC
VCA video analysis, ONVIF event mapping	Wedge adapter included (10° inclination)
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

Camera:		Features:	
Camera type	Dome	e-PTZ support	yes
Sensor size	1/2.5"	Internal storage	microSDHC card, microSDXC card
Resolution standard	4K Ultra HD	Menu languages	English, German, French, Korean
Imager	CMOS, Sony STARVIS, Sensor IMX274	Privacy zones masking	Areas-ON/OFF switchable
System	True Day&Night	Remote configuration	web browser
Sensitivity	0,2 Lux, at F1.5, 40IRE	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Low speed shutter	yes, 1x~10x	User interface	Type A (orange / grey)
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.	Mirror function	mirror, flip
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.	Digital Noise Reduction (DNR)	yes
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR	Network:	
Flickerless function	yes	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Backlight compensation	BLC, HLC	Interfaces / Inputs / Outputs:	
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)	Video outputs	no
IR cut filter	switchable	External connections	RJ-45, 12VDC input (DC plug), connection cable approx.55cm
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes	Ethernet interface	10Base-T, 100Base-TX
Signal-to-noise ratio	50dB	Alarm inputs	no
Video:		Alarm outputs	no
Resolution	3840x2160 (16:9), 2592x1520 (16:9), 1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)	Serial interfaces	Ethernet
Resolution max.	3840x2160	General:	
Stream types	Multi Streaming	Series	eneo Callisto Indoor, eneo LN-Series
Image transmission rate max.	30 fps	Dimensions (HxWxD)	94x116mm
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG	Illumination	infrared, 2x High Power LEDs 850nm
Lens:		Illumination range	approx. 30m
Lens type	Varifocal (motorized)	Colour (housing)	white
Zoom factor	3x	Colour (bubble)	clear
Focal length	3,6 - 11 mm	Housing	indoor
Digital zoom	yes	Housing material	plastic
MOD (Minimum object distance)	0,5 m	Weight	300g
Iris control	DC	Heater	no
Vertical angle of view	46 - 21 °	Power consumption	8,5W
Horizontal angle of view	84 - 40 °	Blower	yes
Features:		Mounting	wall mount, ceiling mount
Multicast compliant	yes	ONVIF	ONVIF Profile S, ONVIF Profile T
Motion detector	yes	Power over Ethernet	IEEE 802.3af
Analysis functions	motion detection, Field detection, Object left, removed, Defog, Line detection	SDK	upon request
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping	Supply voltage	12VDC, PoE
Rotation range	+/-165 °	Temperature range (operation)	-10°C ~ +50°C
Vertical tilt range	+/-60°	Text display	supplied
Audio support	no	Vandalism resistant	yes
Password protection	yes	Scope of delivery:	
		Parts supplied	manual, bag of screws


Product recommendations



IAD-5SG1004MUA|SKU: 216469



IAD-5SG1008MUA|SKU: 216472



eneo Site Manager|SKU: 218218

