

IAM-5SE1008IUA

SKU: 230034



Switch unmanged, 120W, 8xPoE 1xRJ45 ,1xSFP
Gigabit Industrial Design

Main Features

Ethernet PoE Switch, DIN Rail	Surge protection IEC61000-4-5 (6KV)
Gigabit Uplink ports 1xRJ45, 1xSFP	Status LED: Uplink, PoE, Optical port, Power
8x 10/100 PoE Ports,IEEE 802.3af/at	CCTV mode allows transmission up to 250m @ 10Mbps
Up to 30W per port, Total ≤240W (optional power supply)	Temperature range -30° C ~ +65° C

Specifications

Functions:	
Multicast compliant	no
Port mirror	no
QoS	no
SNMP	no
Security	CCTV Mode
Network:	
Ethernet standards	IEEE 802.3 10BaseT,IEEE 802.3u 100BaseTX,IEEE 802.ab 1000BaseT,IEEE 802.3z 1000BaseSX/LX,IEEE 802.3x Flow Control,IEEE 802.3at Power Over Ethernet (PoE+),IEEE 802.3af Power Over Ethernet (PoE)
Internal switching capacity (Mpps)	4,0 Mpps
Internal switching capacity (Gbit/s)	5,6 Gbps

IAM-5SE1008IUA

Continuation of the specifications

VLAN	yes
Interfaces / Inputs/ Outputs:	
Ethernet interface	10Base-T,100Base-TX,1000Base-T
Ports	8x 10/100Base-TX,1x 10/100/1000T SFP,1x 10/100/1000Base-T
Optical connector	SFP Port
General:	
Dimensions (HxWxD)	44x159x110mm
Weight	500g
PoE ports (number)	8
Model	housing
Type	Unmanaged
Blower	no
Management	no
Mounting	desktop
PoE budget	240 W
Power over Ethernet	IEEE 802.3af,IEEE 802.3at
Supply voltage	48~57 VDC
Operating temperature	-30°C ~ 65°C
Trunk	Contact discharge 6KV,Air discharge 8KV,IEC61000-4-2,IEC61000-4-5
Parts supplied:	
Parts supplied	manual,power cord,Mounting Bracket,PSU
Notes:	
Remarks	External power supply specification: 100~240VAC, 120W, -10°~+55°.To achieve the specified PoE budget (total) value, an appropriate optional power supply unit must be used.

Optional Accessory

SKU	Name	Description
219525	RJT-1000SFP	RJ45- SFP Transceiver Modul, 1000Base-T, 0°~+70°C
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216567	SFP-0850MM10	SFP Modul, 155Mbps , 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C

IAM-5SE1008IUA

Continuation of accessory

216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C
--------	-------------	---



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

