


# FH-Series ID

## Multispectral Fixed Camera for Perimeter Security

The FLIR FH-Series ID are ruggedized, multispectral fixed cameras that integrate industry-leading thermal imaging with 4K visible imaging to provide reliable intruder-detection capabilities for perimeter security. Built-in convolutional neural network (CNN) analytics accurately detect and classify human and vehicle threats moving at high or low speeds, minimizing false alarms and daily operations costs. Custom scheduling enables security operators to set intrusion analytics to run on visible streams during the day and on thermal streams throughout the night, establishing optimized coverage for any lighting condition.

**PERIMETER PROTECTION**  
**INTRUSION DETECTION**  
**TARGET GEOLOCATION**  
**OBJECT CLASSIFICATION WITH CNN**  
**ANALYTICS 24/7 SITUATIONAL AWARENESS**  
**CYBERSECURITY HARDENED**  
**SEAMLESS INTEGRATION WITH VMS**



### ALWAYS READY, ALWAYS WORKING

Integrates high-resolution thermal imaging and a visible sensor into a single camera for optimal performance in any environment or lighting condition

- Gain 24/7 situational awareness in the most challenging perimeters with the 640 × 512 thermal imager and market-leading <30 mK thermal sensitivity
- Assess threats in real time and see forensic detail with the 4K visible camera
- Combines a two-camera installation in one physical connection for a cost-efficient solution
- 10-year thermal sensor warranty

### HIGH-ACCURACY INTRUSION DETECTION

Features CNN-based decision support, allowing on-camera video analytics to run on both the visible and thermal spectrum for robust intrusion detection customized for each installation

- Minimize false alarms and the cost of daily operations by detecting and classifying threats (human and vehicle) with high accuracy
- Make detections based on time of day, business hours, and seasonality with the on-board scheduling tool, which allows the operator to select either visible or thermal analytics
- Clearly detect intruders in challenging poses – even when they're only in partial view of the camera or moving at high or low speeds

### EASY INTEGRATION

Deploy this camera as part of a Teledyne FLIR end-to-end solution or in combination with preferred third-party solutions

- Strengthen end-to-end systems with on-board NEXUS® technology, which enables network connections to FLIR edge devices
- Tightly integrated with FLIR United VMS and major third-party VMS
- ONVIF® Conformant to S/G/T profiles

## FH-SERIES ID

Thermal Sensor & Optics				
Array Format (NTSC)	640 × 512			
Detector Type	Long-life, uncooled VOx microbolometer			
Pixel Pitch	17 μm			
Thermal Frame Rate	NTSC: 30 Hz or PAL: 25 Hz / 8.3 Hz			
Optical Characteristics	Model	FOV	Focal Length	F/#
	669	69° × 56°	9 mm	F1.4
	644	44° × 36°	13 mm	F1.0
	625	25° × 18°	25 mm	F1.1
	617	17° × 14°	35 mm	F1.1
	612	12° × 10°	50 mm	F1.2
	610	10° × 8.2°	60 mm	F1.2
	608	8.6° × 6.6°	75 mm	F1.1
Spectral Range	7.5 μm to 13.5 μm			
Sensitivity (NEΔT)	<30 mK @ 25°C (77°F) F# 1.0			
Visible Light Camera				
Sensor Type	4K 2160p (3840 × 2160)			
Optical Characteristics	Model	Default FOV	Focal Length	F/#
	669	98° × 55°	3.6-10 mm	1.5 - 2.8
	644	63° × 35°	3.6-10 mm	1.5 - 2.8
	625	36° × 20°	9-22 mm	1.4 - 1.7
	617	24° × 14°	13-55 mm	1.6 - 2.2
	612	17° × 10°	13-55 mm	1.6 - 2.2
	610	14° × 8°	13-55 mm	1.6 - 2.2
	608	11° × 6°	13-55 mm	1.6 - 2.2
Video				
Video Type	IP or analog video			
Sensitivity	Color: 0.25 Lux (@ f1.6 AGC On, 30 fps) B/W: 0.10 Lux (@ f1.6 AGC On, 30 fps)			
Visible Frame Rate	30 Hz			
Video Compression	Two independent channels of H.264/H.265 or M-JPEG (except 4K) for visible and thermal			
Streaming Resolution	Primary stream: Thermal: VGA (640 × 512), QVGA (320 × 256) Visible: 4K (3840 × 2160), 1080p (1920 × 1080), 720p (1280 × 720) & VGA (640 × 480)			
	Secondary stream: Thermal: VGA (640 × 512), QVGA (320 × 256) Visible: 1080p (1920 × 1080), 720p (1280 × 720) & VGA (640 × 480)			
Thermal Image Settings	Auto AGC, Dynamic Detail Enhancement (DDE), Brightness, Contrast			
Thermal AGC Region of Interest (ROI)	Default, Presets and User definable to ensure optimal image quality on subjects of interest			
Image Uniformity Optimization	Automatic Flat Field Correction (FFC) - Thermal and Temporal Triggers			
System Integration				
Ethernet	100/1000 Mbps			
Network APIs	NEXUS® SDK NEXUS® CGI ONVIF Profile S, G, T			
Digital I/O	Input: two dry alarm contacts Output: two relay contacts 1 A max at 24 VAC/30 VDC Configurable between normally open and normally closed			

Network	
Supported Protocols	IPv4, HTTP, HTTPS, UPnP, DNS, NTP, RTSP, TCP, UDP, ICMP, IGMP, DHCP, ARP, IEEE 802.1X
General	
Input Voltage	12 VDC (±10%) 24 VDC (±10%) 24 VAC (±10%) 802.3 bt
Power Consumption	Nominal: 15 W Heaters enabled, 12 VDC: 48 W Heaters enabled, all other inputs: 70 W
Environmental	
IP Rating (Dust & Water Ingress)	IP66, IP67
Operating Temperature Range	-40°C to 70°C (-40°F to 158°F)
Storage Temperature Range	-55°C to 85°C (-67°F to 185°F)
Corrosion	MIL-STD 810G, 1000 hr salt spray
Humidity	0-95% relative
Shock	IEC 60068-2-27
Vibe	IEC 60068-2-64
Vandalism	IK10 (except Windows)
Surge Immunity on AC Power Lines	EN 50130- 4
Surge Immunity on Signal Lines	EN 50130- 4
Surge/Lightning Protection	TVS 6000 V Lightning protection, surge protection, voltage transient protection
Compliance & Certifications	
FCC Part 15 (Subpart B, class A)	
CE Marked	
RoHS	
IP66	
WEEE	
IEC 62368	
ONVIF Profile S, G, T	
Video Analytics	
Region entrance/Intrusion detection	
Tampering	
Loitering	
CNN classifier	
Cybersecurity	
IEEE 802.1X	
TLS/HTTPS	
User authentication	
Access control via firewall	
User credentials with policy enforcement	
Digest authentication	

## AMERICAS

27700 SW Parkway Ave.  
Wilsonville, OR 97070  
Office: +1 877.773.3547

6769 Hollister Ave.  
Goleta, CA 93117  
Office: +1 805.690.6600

For more information visit:  
[www.flir.com/FH-Series-ID](http://www.flir.com/FH-Series-ID)

[www.teledyneflir.com](http://www.teledyneflir.com)

Imagery for illustration purposes only. Specifications are subject to change without notice. ©2022 Teledyne FLIR LLC, Inc. All rights reserved. 01-2022