

POE304-EX-4P-V2

POE-bt to Gigabit Ethernet 4-port PoE+ Extender

Overview

The IFS POE304-EX-4P-V2 is remotely powered via Ethernet cable from a PoE-bt injecting device eliminating the need for local power requirements. The POE304-EX-4P-V2 can then transmit up to 4-ports of Ethernet data and PoE-af/at power dependent on the Powered Devices (PD) power demand.

The IFS PoE-bt solution facilitates easier network planning by eliminating restrictions of edge device placement near AC power outlets and reducing the need for AC wiring and installation costs.



Einzelheiten

- 4-Port POE+ Switch powered by 1 x POE-bt input (up to 95W)
- Up to 75 watts shared POE power
- Plug-and-play self-powered design
- Can be used with an IFS PoE-Ultra Injector or other POE-bt compliant PSE equipment
- Supports 10/100/1000Base-T Ethernet
- Auto-detect of PoE equipment providing protection from incorrect installation
- Current overload detection
- LED Indicators for PoE In, PoE Out, Data
- Can be daisy-chained to extend data and PoE on a single network cable a maximum of 300m.

POE304-EX-4P-V2

POE-bt to Gigabit Ethernet 4-port PoE+ Extender

Technische Spezifikationen

Allgemein

Kategorie	PoE Verlängerer
Porttyp	10/100/1000
Port-Geschwindigkeit	Gigabit

Elektrische Angaben

Energieverbrauch	75 W
------------------	------

Physikalisch

Abmessungen	32 x 87 x 135 mm
Nettogewicht	430 g

Umweltbedingungen

Betriebstemperatur	-40 to +75°C
Lagertemperatur	-40 to +85°C
Umgebung	Draußen

Ethernet

Max Throughput (packet 7.44Mbps at 64 Bytes per second)	
IEEE Standards	IEEE 802.3 Ethernet / IEEE 802.3u Fast Ethernet / IEEE 802.3ab Gigabit Ethernet
Latency	1765 ns (at 64 Byte Frame)
Maximum Frame Size	9 Kbytes
EIA/TIA-568 Standards	Category 5/5e cable

Power Over Ethernet (PoE)

PoE Standard	IEEE 802.3at
PoE Power Supply Type	POE-bt (No external power adaptor required)
PoE Output Pin	4/5(+), 7/8(-)
Assignment	
PoE Output Power with Multiple Extenders	4 x POE-af/at per port, 75 W max. shared power budget.

Connectors & Indicators

Ethernet + PoE In	1 x RJ-45 connector
Ethernet + PoE Out	4 x RJ-45 connector
LED Indicator	PWR (Green), PoE Power In (Mid-Span/End-Span - 2 x Green), PoE Power Meter (3 x Green), Input Port - LNC/ACT (Green) PoE (Amber), Per Port Output - LNC/ACT (Green) PoE (Amber)

Electrical & Mechanical


Input Power	Powered by POE-bt (PoE Switch or Mid-Span Injector)
Maximum Powered Devices	4
Enclosure	Metal
Power consumption	5 watts from PoE uplink

Environmental

MTBF	>50,000 hrs. @ 25°C
------	---------------------

Standards Compliance

Regulatory	FCC Part 15 Class A, CE
EMI	EN 55022 CLASS A / EN61000-3-2 / EN61000-3-3
EMS	EN 55024 / IEC 61000-4-2 / IEC 61000-4-3 / IEC 61000-4-4 / IEC 61000-4-5 / IEC 61000-4-6 / IEC 61000-4-8 / IEC 61000-4-11 / IEC/EN 60950-1



Dimensions (unit = mm)



Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.