



VZT-21B/TB

Article number: 75802

Passive Twisted Pair Transmitter or Receiver, Compos. In/Output, BNC-T.Block

Transmission via CAT 5e(6) UTP cable

Up to 400m colour / 600m b&w (at unshielded cable)

Approx. 200m colour / 300m b&w (at shielded cable)

No adjustment necessary

Connectors: BNC plug / 2 pin terminal block

Specifications

Signal transmission	video
Operation mode	passive
Dimensions (HxWxD)	22x25x54mm (w./o. BNC plug)
Model	mini module
Range	400 m
Colour	black
Housing	plastic
Type of unit	transmitter / receiver
Weight	30g
Protection rating	n/a
Supply voltage	-
Temperature range (operation)	-5°C ~ +55°C

Preferably unshielded twisted-pair cables should be used for the signal transmission. Are there already existing shielded cables which have to be used, the shield must only be earthed on one end, e. g. on transmitter side. We recommend cables in a twisted 2- pair wire bundle configuration (n2x2x0.8mm). The best result will be achieved by using cables with a twist of up to 7-times per meter. Shielded cables, cables with different wire diam., or a connection via patch fields, can considerably reduce the max. possible transmission length.



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

